

COMP1521 25T2 — Bitwise Operators

<https://www.cse.unsw.edu.au/~cs1521/25T2/>

You Need to Know What Bytes are Representing

What does the byte `0b10100011` mean?

- Does it mean `−93`? (signed 1-byte integer)
- Does it mean `163`? (unsigned 1-byte integer)
- Does it mean something else?

What do the 4 bytes `0b01110011_01110010_01101001_00000000` mean?

- Does it mean `1936877824`? ([un]signed 4-byte int)
- Does it mean $\sim 1.9205 \times 10^{31}$? (IEEE-754 single-precision floating point)
- ... or could it mean `"sri"`? (null-terminated ascii string)

- CPUs typically provide instructions which operate on individual bits of values.
 - MIPS provides 13 bit manipulation instructions
 - other CPUs can provide more
- C provides 6 operators which operate on individual bits of values

```
x & y      // bitwise and
x | y      // bitwise or
x ^ y      // bitwise exclusive-or (XOR)
~ x        // bitwise not
x << n     // left shift
x >> n     // right shift
```

Bitwise AND: &

The **&** operator

- takes two values (1,2,4,8 bytes), treats as sequence of bits
- performs logical AND on each corresponding pair of bits
- result contains same number of bits as inputs

Example:

00100111	AND		0	1
& 11100011	----		-----	
-----			0	0 0
00100011			1	0 1

- Useful for:
 - checking whether a particular bit is set
 - setting particular bit(s) to 0

Checking if a number is odd

Because of how integers are represented, an odd value must have a 1 bit in the 1s place:

For example, the 8-bit representations for **39** and **-47**

128	64	32	16	8	4	2	1	
0	0	1	0	0	1	1	1	39
1	1	0	1	0	0	0	1	-47

```
int is_odd(int n) {
    return n & 1;
}
```

- but should we?
 - no - write obvious readable code
 - rely on compiler to generate fastest assembler
 - if **andi** instruction is faster than **rem**, compiler will generate it
- so we should use this code:

```
int is_odd(int n) {
    return n % 2 != 0;
}
```

Bitwise OR: |

The | operator

- takes two values (1,2,4,8 bytes), treats as sequence of bits
- performs logical OR on each corresponding pair of bits
- result contains same number of bits as inputs

Example:

00100111	OR 0 1
11100011	---- -----
-----	0 0 1
11100111	1 1 1

- Useful for:
 - setting particular bit(s) to 1

Bitwise NEG: ~

The ~ operator

- takes a single value (1,2,4,8 bytes), treats as sequence of bits
- performs logical negation of each bit
- result contains same number of bits as input

Example:

~ 00100111	NEG 0 1
-----	---- -----
11011000	1 0

- Useful for:
 - creating particular bit patterns

The ^ operator

- takes two values (1,2,4,8 bytes), treats as sequence of bits
- performs logical XOR on each corresponding pair of bits
- result contains same number of bits as inputs

Example:

```

00100111      XOR | 0  1
^ 11100011      ----|-----
-----      0  | 0  1
11000100      1  | 1  0

```

- Useful for:
 - generating hashes
 - cryptography
 - graphics operations

Left Shift: <<

The << operator

- takes a single value (1,2,4,8 bytes), treats as sequence of bits
- also takes a small positive integer x
- moves (shifts) each bit x positions to the left
- left-end bit vanishes; right-end bit replaced by zero

Example:

```

00100111 << 2      00100111 << 8
-----      -----
10011100      00000000

```

- Useful for:
 - creating particular bit patterns
 - multiplying by power of two

Right Shift: >>

The >> operator

- takes a single value (1,2,4,8 bytes), treats as sequence of bits
- also takes a small positive integer x
- moves (shifts) each bit x positions to the right
- right-end bit vanishes; left-end bit replaced by zero(*)
- shifts involving negative values are not portable (implementation defined)
- common source of bugs in COMP1521 and elsewhere
- always use unsigned values/variables to be safe/portable.

Example:

```

00100111 >> 2      00100111 >> 8
-----      -----
00001001      00000000

```

- Useful for:
 - loops which need to process one bit at a time
 - dividing by power of two

assembly	meaning	bit pattern
and r_d, r_s, r_t	$r_d = r_s \& r_t$	000000ssssstttttddddd00000100100
or r_d, r_s, r_t	$r_d = r_s \mid r_t$	000000ssssstttttddddd00000100101
xor r_d, r_s, r_t	$r_d = r_s \wedge r_t$	000000ssssstttttddddd00000100110
nor r_d, r_s, r_t	$r_d = \sim(r_s \mid r_t)$	000000ssssstttttddddd00000100111
andi r_t, r_s, I	$r_t = r_s \& I$	001100ssssstttttIIIIIIIIIIIIIIII
ori r_t, r_s, I	$r_t = r_s \mid I$	001101ssssstttttIIIIIIIIIIIIIIII
xori r_t, r_s, I	$r_t = r_s \wedge I$	001110ssssstttttIIIIIIIIIIIIIIII
not r_d, r_s	$r_d = \sim r_s$	pseudo-instruction

- mipsy translates **not** r_d, r_s to **nor** $r_d, r_s, \$0$

MIPS - Shift Instructions

assembly	meaning	bit pattern
sllv r_d, r_t, r_s	$r_d = r_t \ll r_s$	000000ssssstttttddddd00000000100
srlv r_d, r_t, r_s	$r_d = r_t \gg r_s$	000000ssssstttttddddd00000000110
sra r_d, r_t, r_s	$r_d = r_t \gg r_s$	000000ssssstttttddddd00000000111
sll r_d, r_t, I	$r_d = r_t \ll I$	000000000000tttttdddddIIIIII000000
srl r_d, r_t, I	$r_d = r_t \gg I$	000000000000tttttdddddIIIIII000010
sra r_d, r_t, I	$r_d = r_t \gg I$	000000000000tttttdddddIIIIII000011

- **srl** and **srlv** shift zeros into most-significant bit
 - this matches shift in C of **unsigned** value
- **sra** and **sra** propagate most-significant bit
 - this ensure shifting a negative number divides by 2
- mipsy provides **rol** and **ror** pseudo-instructions which rotate bits
 - real instructions on some MIPS versions
 - no simple C equivalent

bitwise.c: showing results of bitwise operation

```
$ gcc bitwise.c print_bits.c -o bitwise
$ ./bitwise
Enter a: 23032
Enter b: 12345
Enter c: 3
    a = 0101100111111000 = 0x59f8 = 23032
    b = 0011000000111001 = 0x3039 = 12345
    ~a = 1010011000000111 = 0xa607 = 42503
a & b = 0001000000111000 = 0x1038 = 4152
a | b = 0111100111111001 = 0x79f9 = 31225
a ^ b = 0110100111000001 = 0x69c1 = 27073
a >> c = 0000101100111111 = 0x0b3f = 2879
a << c = 1100111111000000 = 0xcfc0 = 53184
```

source code for bitwise.c

source code for print_bits.c source code for print_bits.h

[source code for bitwise.c](#)

<https://www.cse.unsw.edu.au/~cs1521/25T2/>

source code for shift as multiply.c

20 / 49

21 / 49

print_bits.c: extracting the n-th bit of a value

```
// print the bottom how_many_bits bits of value
void print_bits(uint64_t value, int how_many_bits) {
    // print bits from most significant to least significant
    for (int i = how_many_bits - 1; i >= 0; i--) {
        int bit = get_nth_bit(value, i);
        printf("%d", bit);
    }
}
```

```
// extract the nth bit from a value
int get_nth_bit(uint64_t value, int n) {
    // shift the bit right n bits
    // this leaves the n-th bit as the least significant bit
    uint64_t shifted_value = value >> n;
    // zero all bits except the the least significant bit
    int bit = shifted_value & 1;
    return bit;
}
```

print_int_in_hex.c: print an integer in hexadecimal

- write C to print an integer in hexadecimal instead of using:

```
printf("%x", n)
```

```
$ gcc print_int_in_hex.c -o print_int_in_hex
$ ./print_int_in_hex
Enter a positive int: 42
42 = 0x0000002A
$ ./print_int_in_hex
Enter a positive int: 65535
65535 = 0x0000FFFF
$ ./print_int_in_hex
Enter a positive int: 3735928559
3735928559 = 0xDEADBEEF
$
```

source code for print_int_in_hex.c

print_int_in_hex.c: main

```
int main(void) {
    uint32_t a = 0;
    printf("Enter a positive int: ");
    scanf("%u", &a);
    printf("%u = 0x", a);
    print_hex(a);
    printf("\n");
    return 0;
}
```

source code for print_int_in_hex.c

print_int_in_hex.c: print_hex - extracting digit

```
// sizeof returns number of bytes in n's representation
// each byte is 2 hexadecimal digits
int n_hex_digits = 2 * (sizeof n);
// print hex digits from most significant to least significant
for (int which_digit = n_hex_digits - 1; which_digit >= 0; which_digit--) {
    // shift value across so hex digit we want
    // is in bottom 4 bits
    int bit_shift = 4 * which_digit;
    uint32_t shifted_value = n >> bit_shift;
    // mask off (zero) all bits but the bottom 4 bites
    int hex_digit = shifted_value & 0xF;
    // hex digit will be a value 0..15
    // obtain the corresponding ASCII value
    // "0123456789ABCDEF" is a char array
    // containing the appropriate ASCII values (+ a '\0')
    int hex_digit_ascii = "0123456789ABCDEF"[hex_digit];
    putchar(hex_digit_ascii);
}
```

source code for print_int_in_hex.c

<https://www.cse.unsw.edu.au/~cs1521/25T2/>

COMP1521 25T2 — Bitwise Operators

28 / 49

int_to_hex_string.c: convert int to a string of hex digits

- Write C to convert an integer to a string containing its hexadecimal digits.

Could use the C library function `snprintf` to do this.

```
$ gcc int_to_hex_string.c -o int_to_hex_string
$ ./int_to_hex_string
$ ./int_to_hex_string
Enter a positive int: 42
42 = 0x0000002A
$ ./int_to_hex_string
Enter a positive int: 65535
65535 = 0x0000FFFF
$ ./int_to_hex_string
Enter a positive int: 3735928559
3735928559 = 0xDEADBEEF
$
```

source code for int_to_hex_string.c

<https://www.cse.unsw.edu.au/~cs1521/25T2/>

COMP1521 25T2 — Bitwise Operators

29 / 49

int_to_hex_string.c: main

```
int main(void) {
    uint32_t a = 0;
    printf("Enter a positive int: ");
    scanf("%u", &a);
    char *hex_string = int_to_hex_string(a);
    // print the returned string
    printf("%u = 0x%s\n", a, hex_string);
    free(hex_string);
    return 0;
}
```

source code for int_to_hex_string.c

<https://www.cse.unsw.edu.au/~cs1521/25T2/>

COMP1521 25T2 — Bitwise Operators

30 / 49

int_to_hex_string.c: convert int to a string of hex digits

```
// sizeof returns number of bytes in n's representation
// each byte is 2 hexadecimal digits
int n_hex_digits = 2 * (sizeof n);
// allocate memory to hold the hex digits + a terminating 0
char *string = malloc(n_hex_digits + 1);
// print hex digits from most significant to least significant
for (int which_digit = 0; which_digit < n_hex_digits; which_digit++) {
    // shift value across so hex digit we want
    // is in bottom 4 bits
    int bit_shift = 4 * which_digit;
    uint32_t shifted_value = n >> bit_shift;
    // mask off (zero) all bits but the bottom 4 bits
    int hex_digit = shifted_value & 0xF;
    // hex digit will be a value 0..15
    // obtain the corresponding ASCII value
    // "0123456789ABCDEF" is a char array
    // containing the appropriate ASCII values
    int hex_digit_ascii = "0123456789ABCDEF"[hex_digit];
    int string_position = n_hex_digits - which_digit - 1;
    string[string_position] = hex_digit_ascii;
}
// 0 terminate the array
string[n_hex_digits] = 0;
return string;
```

source code for int_to_hex_string.c

<https://www.cse.unsw.edu.au/~cs1521/25T2/>

COMP1521 25T2 — Bitwise Operators

31 / 49

hex_string_to_int.c: convert hex digit string to int

- As an exercise write C to convert an integer to a string containing its hexadecimal digits.

Could use the C library function `strtol` to do this.

```
$ gcc hex_string_to_int.c -o hex_string_to_int
$ gcc hex_string_to_int.c -o hex_string_to_int
$ ./hex_string_to_int 2A
2A hexadecimal is 42 base 10
$ ./hex_string_to_int FFFF
FFFF hexadecimal is 65535 base 10
$ ./hex_string_to_int DEADBEEF
DEADBEEF hexadecimal is 3735928559 base 10
$
```

source code for hex_string_to_int.c

<https://www.cse.unsw.edu.au/~cs1521/25T2/>

COMP1521 25T2 — Bitwise Operators

32 / 49

hex_string_to_int.c: main

```
int main(int argc, char *argv[]) {
    if (argc != 2) {
        fprintf(stderr, "Usage: %s <hexadecimal-number>\n", argv[0]);
        return 1;
    }
    char *hex_string = argv[1];
    uint32_t u = hex_string_to_int(hex_string);
    printf("%s hexadecimal is %u base 10\n", hex_string, u);
    return 0;
}
```

source code for hex_string_to_int.c

<https://www.cse.unsw.edu.au/~cs1521/25T2/>

COMP1521 25T2 — Bitwise Operators

33 / 49

```
uint32_t hex_string_to_int(char *hex_string) {
    uint32_t value = 0;
    for (int i = 0; hex_string[i] != 0; i++) {
        int ascii_hex_digit = hex_string[i];
        int digit_as_int = hex_digit_to_int(ascii_hex_digit);
        value = value << 4;
        value = value | digit_as_int;
    }
    return value;
}
```

source code for hex_string_to_int.c

hex_string_to_int.c: convert single hex digit to int

```
int hex_digit_to_int(int ascii_digit) {
    if (ascii_digit >= '0' && ascii_digit <= '9') {
        // the ASCII characters '0' .. '9' are contiguous
        // in other words they have consecutive values
        // so subtract the ASCII value for '0' yields the corresponding integer
        return ascii_digit - '0';
    }
    if (ascii_digit >= 'A' && ascii_digit <= 'F') {
        // for characters 'A' .. 'F' obtain the
        // corresponding integer for a hexadecimal digit
        return 10 + (ascii_digit - 'A');
    }
    fprintf(stderr, "Bad digit '%c'\n", ascii_digit);
    exit(1);
}
```

source code for hex_string_to_int.c

shift_bug.c: bugs to avoid

```
// int16_t is a signed type (-32768..32767)
// below operations are undefined for a signed type
int16_t i;
i = -1;
i = i >> 1; // undefined - shift of a negative value
printf("%d\n", i);
i = -1;
i = i << 1; // undefined - shift of a negative value
printf("%d\n", i);
i = 32767;
i = i << 1; // undefined - left shift produces a negative value
uint64_t j;
j = 1 << 33; // undefined - constant 1 is an int
j = ((uint64_t)1) << 33; // ok
```

source code for shift_bug.c

xor.c: fun with xor

```
int xor_value = strtol(argv[1], NULL, 0);
if (xor_value < 0 || xor_value > 255) {
    fprintf(stderr, "Usage: %s <xor-value>\n", argv[0]);
    return 1;
}
int c;
while ((c = getchar()) != EOF) {
    //     exclusive-or
    //     ^ | 0 1
    //     ----|-----
    //     0 | 0 1
    //     1 | 1 0
    int xor_c = c ^ xor_value;
    putchar(xor_c);
}
```

source code for xor.c

<https://www.cse.unsw.edu.au/~cs1521/25T2/>

COMP1521 25T2 — Bitwise Operators

37 / 49

xor.c: fun with xor

```
$ echo Hello Andrew|xor 42
bOFFE
kDNXO] $ echo Hello Andrew|xor 42|cat -A
bOFFE$
kDNXO] $
$ echo Hello |xor 42
bOFFE $ echo -n 'bOFFE '|xor 42
Hello
$ echo Hello|xor 123|xor 123
Hello
$
```

<https://www.cse.unsw.edu.au/~cs1521/25T2/>

COMP1521 25T2 — Bitwise Operators

38 / 49

pokemon.c: using an int to represent a set of values

```
#define FIRE_TYPE      0x0001
#define FIGHTING_TYPE  0x0002
#define WATER_TYPE     0x0004
#define FLYING_TYPE    0x0008
#define POISON_TYPE    0x0010
#define ELECTRIC_TYPE  0x0020
#define GROUND_TYPE    0x0040
#define PSYCHIC_TYPE   0x0080
#define ROCK_TYPE      0x0100
#define ICE_TYPE       0x0200
#define BUG_TYPE       0x0400
#define DRAGON_TYPE    0x0800
#define GHOST_TYPE     0x1000
#define DARK_TYPE      0x2000
#define STEEL_TYPE     0x4000
#define FAIRY_TYPE     0x8000
```

source code for pokemon.c

<https://www.cse.unsw.edu.au/~cs1521/25T2/>

COMP1521 25T2 — Bitwise Operators

39 / 49

pokemon.c: using an int to represent a set of values

- simple example of a single integer specifying a set of values
- interacting with hardware often involves this sort of code

```
uint16_t our_pokemon = BUG_TYPE | POISON_TYPE | FAIRY_TYPE;
```

```
// example code to check if a pokemon is of a type:
if (our_pokemon & POISON_TYPE) {
    printf("Poisonous\n"); // prints
}
if (our_pokemon & GHOST_TYPE) {
    printf("Scary\n"); // does not print
}
```

source code for pokemon.c

pokemon.c: using an int to represent a set of values

```
// example code to add a type to a pokemon
our_pokemon |= GHOST_TYPE;
// example code to remove a type from a pokemon
our_pokemon &= ~ POISON_TYPE;
```

```
printf(" our_pokemon type (2)\n");
if (our_pokemon & POISON_TYPE) {
    printf("Poisonous\n"); // does not print
}
if (our_pokemon & GHOST_TYPE) {
    printf("Scary\n"); // prints
}
```

source code for pokemon.c

bitset.c: using an int to represent a set of values

```
$ gcc bitset.c print_bits.c -o bitset
$ ./bitset
Set members can be 0-63, negative number to finish
Enter set a: 1 2 4 8 16 32 -1
Enter set b: 5 4 3 33 -1
a = 00000000000000000000000000000000100000000000000010000000100010110 = 0x100010116 = 429!
b = 000000000000000000000000000000001000000000000000000000000000111000 = 0x200000038 = 858!
a = {1,2,4,8,16,32}
b = {3,4,5,33}
a union b = {1,2,3,4,5,8,16,32,33}
a intersection b = {4}
cardinality(a) = 6
is_member(42, a) = 0
```

```

printf("Set members can be 0-%d, negative number to finish\n",
      MAX_SET_MEMBER);
set a = set_read("Enter set a: ");
set b = set_read("Enter set b: ");
print_bits_hex("a = ", a);
print_bits_hex("b = ", b);
set_print("a = ", a);
set_print("b = ", b);
set_print("a union b = ", set_union(a, b));
set_print("a intersection b = ", set_intersection(a, b));
printf("cardinality(a) = %d\n", set_cardinality(a));
printf("is_member(42, a) = %d\n", (int)set_member(42, a));

```

source code for bitset.c

bitset.c: common set operations

```

set set_add(int x, set a) {
    return a | ((set)1 << x);
}

```

```

set set_union(set a, set b) {
    return a | b;
}

```

```

set set_intersection(set a, set b) {
    return a & b;
}

```

```

// return 1 iff x is a member of a, 0 otherwise
int set_member(int x, set a) {
    assert(x >= 0 && x <= MAX_SET_MEMBER);
    return (a >> x) & 1;
}

```

bitset.c: counting set members

```

// return size of set
int set_cardinality(set a) {
    int n_members = 0;
    while (a != 0) {
        n_members += a & 1;
        a >>= 1;
    }
    return n_members;
}

```

```

set set_read(char *prompt) {
    printf("%s", prompt);
    set a = EMPTY_SET;
    int x;
    while (scanf("%d", &x) == 1 && x >= 0) {
        a = set_add(x, a);
    }
    return a;
}

```

bitset.c: set output

```

// print out member of the set in increasing order
// for example {5,11,56}
void set_print(char *description, set a) {
    printf("%s", description);
    printf("{");
    int n_printed = 0;
    for (int i = 0; i <= MAX_SET_MEMBER; i++) {
        if (set_member(i, a)) {
            if (n_printed > 0) {
                printf(",");
            }
            printf("%d", i);
            n_printed++;
        }
    }
    printf("}\n");
}

```

Exercise: Bitwise Operations

Given the following variable declarations:

```

// a signed 8-bit value
unsigned char x = 0x55;
unsigned char y = 0xAA;

```

What is the value of each of the following expressions:

- $(x \& y) \ (x \wedge y)$
- $(x \ll 1) \ (y \ll 1)$
- $(x \gg 1) \ (y \gg 1)$

Assuming 8-bit quantities and writing answers as 8-bit bit-strings:

What are the values of the following:

- 25, 65, ~ 0 , $\sim \sim 1$, 0xFF, $\sim 0xFF$
- $(01010101 \ \& \ 10101010)$, $(01010101 \ | \ 10101010)$
- $(x \ \& \ \sim x)$, $(x \ | \ \sim x)$

How can we achieve each of the following:

- ensure that the 3rd bit from the RHS is set to 1
- ensure that the 3rd bit from the RHS is set to 0