

COMP(2041|9044) 26T2 — Linux

<https://www.cse.unsw.edu.au/~cs2041/26T2/>

building a tiny Linux system

- Linux most widely-used operating system
 - 24 official supported hardware platforms
 - also many variants, including Android, FireOS & ChromeOS
- lets look at compiling and running a tiny linux system from source
- we'll introduce some useful tools (make, qemu, mkfs, ...)
- and important concepts (kernel, filesystems, emulators, ...)
- demo is based on the ARM architecture, if you use x86, follow instructions in the following slides
 - <https://cgi.cse.unsw.edu.au/~cs2041/26T1/topic/linux/slides>

The root user

- Many system actions require root (`uid == 0`)
- **su** allows you to execute commands as root or any other user.
- **sudo** allows command to be run as root
- Use cautiously - easy to damage system with commands run as root.
- Edit sudo config file `/etc/sudoers` with **visudo**

```
# Adding user to sudo group should allow them to run sudo
$ adduser haibo sudo
```

building a tiny Linux system - tools needed

- all the software we'll be using is open source and already installed on CSE servers
- if you want to try out these examples on your own machine, on Debian install these packages:
 - the package names may be different on other systems (Ubuntu, WSL, ...)

```
$ sudo apt update
$ sudo apt install bc bison build-essential curl flex fuse2fs libelf-dev
↪ libssl-dev qemu-system qemu-user
```

- build-essential is a meta-package which installs many other packages - for tools often used in building software
 - e.g. gcc, make

qemu - a vmachine emulator

- qemu is an open-source emulator
 - can emulate instruction sets including x86, MIPS, 32-bit ARMv7, ARMv8, PowerPC, RISC-V, ...
 - uses clever techniques to make emulation fast but still significant overhead
- can emulate execution of a single (linux) program - user mode emulation
 - e.g. can emulate MIPS code on an x86 box
 - operating system is still the host operating system
 - e.g. can't run windows executables on linux
- can emulate an entire (virtual) machine - system emulation
 - including CPU, RAM, display, disks, network ...
 - can boot another operating system, e.g. can emulate Windows on a Linux box
 - often more convenient for development than real hardware
 - we'll build some tiny linux systems and run them with qemu
- qemu also provides virtualization - virtual machine with (almost) no overhead
 - virtualization needs hardware support & OS support
 - virtual machine must be same architecture (e.g. x86) as host
 - other virtualization implementations: virtualbox, vmware, Microsoft Virtual PC

what is a cross compiler

- a cross compiler is a compiler which generates machine code for a different platform
 - e.g. a cross compiler might run on x86 (Intel) but generate code for MIPS
 - allows you build software on a powerful general purpose machine (e.g laptop)
 - and deploy to special-purpose machine e.g. a router

qemu user mode example - simple test program

```
// print the nth-prime
#include <stdio.h>
#include <stdlib.h>
int is_prime(int number) {
    for (int possible_factor = 2; possible_factor < number; possible_factor++)
    {
        if (number % possible_factor == 0) {
            return 0;
        }
    }
    return 1;
}
int main(int argc, char *argv[]) {
    int n = atoi(argv[1]);
    int n_primes = 0;
    for (int number = 2; n_primes < n; number++) {
        n_primes += is_prime(number);
        if (n_primes == n) {
            printf("%d\n", number);
            return 0;
        }
    }
}
```

[source code for nth_prime.c](#)

qemu user mode example - running our test program

```
# a simple program to print the nth prime
$ gcc -O3 nth_prime.c -o nth_prime
$ file nth_prime
nth_prime: ELF 64-bit LSB pie executable, ARM aarch64, version 1 (SYSV),
  ↪ dynamically linked, interpreter /lib/ld-linux-aarch64.so.1, ...
$ time ./nth_prime 10000
104729
real    0m0.643s
```


qemu user mode example - a complication - dynamic linking

- **nth_prime** is dynamically linked
- **nth_prime** does not contain the code for the C library (e.g. printf)
- when run **nth_prime** is linked with C library code by the operating system
 - this allows operating system to share C library code in RAM between many programs
 - can upgrade (bug/security) fix library without recompiling programs which use library
 - saves disk space
- **ldd** is useful program - shows how linking will occur when program run

```
$ file nth_prime
```

```
nth_prime: ELF 64-bit LSB pie executable, ARM aarch64, version 1 (SYSV), dynamic
```

```
$ ldd nth_prime
```

```
linux-vdso.so.1 (0x0000ffffb442c000)
```

```
libc.so.6 => /lib/aarch64-linux-gnu/libc.so.6 (0x0000ffffb4200000)
```

```
/lib/ld-linux-aarch64.so.1 (0x0000ffffb43f0000)
```

```
# nth_prime only links in two libraries, other programs may link many
```

qemu user mode example - static compilation

- dynamic linking offers large benefits but breaks if we run the program without libraries present
 - this is problem for emulation and in some other contexts
- gcc/clang has a **-static** option to include all library code in the binary (will be larger)

```
# cross-compile C to x86 machine code instead ARM
```

```
$apt install gcc-x86-64-linux-gnu
```

```
$ x86_64-linux-gnu-gcc -static nth_prime.c -O2 -o nth_prime_x86
```

```
# nth_prime.arm contains ARM machine code
```

```
$ file nth_prime_x86
```

```
nth_prime_x86 : ELF 64-bit LSB executable, x86-64, version 1 (GNU/Linux), ...
```

```
# we are on ARM, we can't run nth_prime_x86 directly but qemu-x86_64 can emulate
```

```
$ time qemu-x86_64 ./nth_prime_x86 10000
```

```
104729
```

```
real    0m1.251s
```

- note emulation is 50% slower than our previous native execution

reminder: curl - interact with web-servers

- **curl** lets you interact from command line with web and other http/https servers
 - curl has many other options & features, **wget** provides similar functionality
 - Andrew likes curl better than wget - but little difference for most tasks
 - busybox provides a cut-down wget

```
# fetch a file
$ curl -O https://cgi.cse.unsw.edu.au/~cs2041/examples.zip
# get other info
$ curl -I https://unsw.edu.au
HTTP/1.1 200 OK
Server: Apache/2.4.34 (Red Hat) OpenSSL/1.0.1e-fips PHP/5.6.25
X-Powered-By: PHP/5.6.25
# send data to web server
$ curl -X PUT -H 'content-type: txt/plain' https://google.com
# send cookies to web server
$ curl -b 'id=42' https://google.com
....
```

- qemu can simulate an entire computer - a virtual machine
- use for virtual machines include:
 - running a different OS, e.g. running windows VM on linux
 - running potentially malicious software safely in isolation
- can host multiple VM on one physical machine
- possible to move running VMs between physical machines

virtual machine example - running ARM OpenWrt on x86

- OpenWRT is popular linux-based operating system for routers and other embedded devices

[illegible]

tar - archive/unarchive files and directories

- tar - widely used tool to create or extract archive files (in tar format)
- An archive file captures metadata and contents of multiple files and directories as a single file
- often incorporates compression
- example file formats include:
 - **tar** - general purpose, Unix-like systems
 - **zip** - general purpose, many platforms, includes compression
 - **deb** - software packages, Debian-family Linux distributions
 - **ar** - used for libraries of relocatable binaries (.o files)
 - **shar** - usually software packages, Unix-like systems
 - self-extracting shell-script!
 - **cpio** - mostly obsolete, general purpose, Unix-like systems, some remaining niche uses (Linux kernel ramdisks)

tar - example

```
# capture files in assignment directory tree
# -c create an archive
# -f archive filename
# -z compress with gzip
$ tar -zcf assignment.tar.gz assignment
$ cp assignment.tar.gz /tmp
$ cd /tmp
# extract files from archive
# -x extract an archive
# -v (verbose) - print filenames when extracting
# -f archive filename
$ tar -xvf assignment.tar.gz
...
```

tar uses compression formats available as external programs and compatible with these programs.

- xz/unxz (-J option to tar)
 - algorithm Lempel–Ziv–Markov-chain
 - good level of compression
 - slow to compress but uncompression fast
- bzip2/bunzip2 (-j option to tar)
 - algorithm: Burrows–Wheeler algorithm
 - faster to compress than xz but compression level not as good
- gzip/gunzip (-z option to tar)
 - algorithm: DEFLATE
 - compression level not as good as bzip2
 - very widely available on Unix-like machines
 - used for HTTP compression

downloading Linux

- Linux source is over 1.3 gigabytes
 - 80,000 separate files, 30 million lines of C source
 - compressed with xz only 136 Mb
 - tar recognises the xz compression automatically - don't need to use unxz

```
$ curl -sO https://cdn.kernel.org/pub/linux/kernel/v7.x/linux-7.0.tar.gz
$ ls -l linux-7.0.tar.gz
-rw-rw-r-- 1 root root 254937830 Apr 21 09:34 linux-7.0.tar.gz
$ tar xf linux-7.0.tar.gz
$ cd linux-7.0
$ find . -type f | wc -l
92939
$ find . -name '*.ch'|xargs cat|wc -l
36485277
# can download and extract with single pipeline, but must specify compression
$ curl https://cdn.kernel.org/pub/linux/kernel/v7.x/linux-7.0.tar.gz|tar -Jxf
↵ -
```

configuration

- portable software often has one or more initial configuration steps
 - user specifies how they want system build
 - scripts set up build for this platform
- Linux uses make + custom scripts for configuration

```
$ find . -name Makefile|wc -l
3184
$ find . -name '*.sh'|wc -l
1090
```

- The configuration step for Linux creates a custom file named **.config**

```
$ make defconfig
...
# configuration written to .config
$ wc .config
5477 17210 146728 .config
```

a smaller configuration

- `make defconfig` builds a `.config` including all Linux code (drivers) for this platform
- This includes many many feature we don't need for our experiments with a tiny linux system.
- Lets download a `.config` which only enables the sort features we need for our experiments
- This will make our build faster and our kernel (Linux compiled binary) smaller

```
$ curl -sL  
  ↪ https://raw.githubusercontent.com/buildroot/buildroot/master/board/qemu/  
aarch64-virt/linux.config >.config
```

```
$ make olddefconfig  
# configuration written to .config
```

compiling Linux

- we can compile the entire Linux kernel just by running `make` - but even on a fast machine takes 8 minutes!
- **`make -j`** where possible runs builds in parallel
 - possible because of the specification of dependencies in Makefiles
- **`make -j8`** 7x faster on a machine with 8+ cores

```
$ time make
...
OBJCOPY arch/arm64/boot/Image
GZIP     arch/arm64/boot/Image.gz
...
real    8m19.669s
$ make clean
$ time make -j8
...
OBJCOPY arch/arm64/boot/Image
GZIP     arch/arm64/boot/Image.gz
...
real    1m11.791s
```

```
$ cd ..  
$ cp linux-7.0/arch/arm64/boot/Image mykernel  
$ ls -l mykernel  
-rw-rw-r-- 1 root root 6693888 Apr 21 09:49 mykernel  
  
$ file mykernel  
mykernel: Linux kernel ARM64 boot executable Image, little-endian, 4K pages
```

- we have an operating system for our tiny system

side note: make - incremental builds

- **make** only rebuilds where files have changed
 - typically we work on only a few files, so make can save a lot of build time

```
# make a (silly) change to 1 of the kernel's 30,000 sources files
$ cd linux-7.0
$ echo '// I miss VGA' >> arch/arm64/boot/video-vga.c
$ time make -j8
...
CC      arch/arm64/boot/video-vga.o
...
real    0m12.709s
```

make only rebuilt the part of the of the kernel that depended on `video-vga.c`

side note: make clean

- makefiles also provide a simple way to specify convenient actions
 - a **make clean** rule is common - removes intermediate compiled files
 - handy to save disk space with you are finished building
 - building Linux kernel create 400mb of intermediate compiled files

```
$ du -s .  
2200756 .  
$ make clean  
...  
$ du -s .  
1776084 .
```

running our kernel in a Virtual Machine with QEMU

```
# -append passes options to the kernel
# -display none -serial stdio runs the virtual machine within our terminal
$ qemu-system-aarch64 -machine virt -cpu max -nographic -kernel mykernel
Booting Linux on physical CPU 0x000000000000 [0x000f0510]
Linux version 7.0.0 (root@d359e0042f2a)
CPU features: detected: ARMv8.4 Translation Table Level
signal: max sigframe size: 1040
BIOS-provided physical RAM map:
...
VFS: Cannot open root device "(null)" or unknown-block(0,0): error -6
Please append a correct "root=" boot option; here are the available
↪ partitions:
---[ end Kernel panic - not syncing: VFS: Unable to mount root fs on
↪ unknown-block(0,0) ]---
```

Our kernel boots but we need to give it a filesystem

- a filesystem is a method used to organize storage of files & directories on a storage device - a storage device (e.g. SSD) typically provides an array of fixed-size blocks
 - 512 KB is a typical blocks size
- a filesystem must track for each file where it is stored
 - in other words which blocks are used for the file
- a filesystem must also track free space - which blocks are unused

- **ext4** - mostly widely used general-purpose Linux filesystem
- **ext2/ext3** - ext4 predecessors with less features but still often used
- **btrfs** - copy-on-write filesystem with interesting features
- **zfs** - filesystem with interesting features including can span disks
- **ntfs** default Windows filesystem - can be accessed from Linux
- **vfat** - older Windows filesystem
 - widely used for removable devices such as SD cards and USB keys
- **nfs** - network filesystem used to provide remote access to files
- **sshfs** - remote filesystem layered on ssh
 - you can use to access your CSE files at home

Creating A Virtual Disk

- we'll create a virtual ext2 filesystem
- ext2 and many other file systems store data in an array of blocks
 - blocks often 4096 bytes
- normally blocks provided by physical disk via a special file, e.g

```
$ ls -l /dev/vda  
brw-rw-rw- 1 root root 254, 0 Jul 30 02:28 /dev/vda
```

- we'll use a normal file instead for our virtual (pretend) disk

```
# fallocate is an convenient and efficient way to create a 128 Mb file  
$ fallocate -l 128M mydisk  
$ ls -l mydisk  
-rw-rw-r-- 1 root root 134217728 Apr 21 09:51 mydisk
```

Creating A Filesystem with mkfs

- mkfs creates an initial filesystem with no files or directories
- **Beware:** mkfs overwrites (destroys) contents of disk - potential huge data loss!

```
# install mkfs
$apt install e2fsprogs
$ mkfs.ext2 mydisk
mke2fs 1.47.0 (4-Aug-1997)
Creating filesystem with 20480 1k blocks and 5112 inodes
Filesystem UUID: a59742a0-464e-4b07-9919-6cb8d01ca8be
Superblock backups stored on blocks:
    8193

Allocating group tables: done
Writing inode tables: done
Writing superblocks and filesystem accounting information: done

$ file mydisk
mydisk: Linux rev 1.0 ext2 filesystem data, ...
```

running our kernel in a Virtual Machine with our new Virtual Disk

```
# -drive file=mydisk,format=raw  tells qemu to use our virtual disk
# root=/dev/sda  tells Linux to use the virtual disk for its root filesystem
$ qemu-system-aarch64 -machine virt -cpu max -drive file=mydisk -nographic
  ↪ -kernel mykernel -append 'root=/dev/vda rw rootwait'

...
EXT4-fs (vda): mounting ext2 file system using the ext4 subsystem
EXT4-fs (vda): warning: mounting unchecked fs, running e2fsck is recommended
EXT4-fs (vda): mounted filesystem cca9881c-c2e2-47c0-9e2b-be2baa2946f4 r/w
  ↪ without journal. Quota mode: disabled.
VFS: Mounted root (ext2 filesystem) on device 254:0.
...
Kernel panic - not syncing: No working init found.
...
```

- our kernel mounts the filesystem but can not find init
- init is the first program run by unix-like systems before it starts other programs

A Toy Init

```
$ cat >myinit.c <<eof
#include <stdio.h>
#include <linux/reboot.h>
#include <sys/reboot.h>

int main(void) {
    printf("hello from myinit\n");
    reboot(LINUX_REBOOT_CMD_POWER_OFF);
}
eof
$ gcc myinit.c -o myinit
$ ls -l myinit
-rwxr-xr-x 1 root root 15952 Jul 27 12:40 myinit
$ ldd myinit
    linux-vdso.so.1 (0x0000ffff86cac000)
    libc.so.6 => /lib/aarch64-linux-gnu/libc.so.6 (0x0000ffff86a80000)
    /lib/ld-linux-aarch64.so.1 (0x0000ffff86c70000)
# above binary is dynamically linked which is inconvenient
# because it needs libraries to run, so lets make a static binary
$ gcc myinit.c -static -o myinit
$ ls -l myinit
-rwxrwxr-x 1 root root 769256 Apr 21 09:54 myinit
```

mount - mount a filesystem

- mount makes the files/directories of a filesystem available below a mount point
 - mount point must be an existing directory
- umount reverses this.

```
$ mkdir mnt
$ mount mydisk mnt
$ ls -l mnt
drwx----- 2 root root 16384 Jul 30 02:49 lost+found

$ umount mnt
```

- distributions typically include a helper program to mount & unmount removable devices.
- mount needs root privileges, fine on your own computer not possible at CSE
- we'll **fuse2fs** instead - which can be run by a regular user, including at CSE

copy myinit to the filesystem on our virtual disk

```
$ ls -l mnt
total 0
$ fuse2fs -o fakeroot mydisk mnt
# our new file system contains only 1 directory: lost+found
# which is pre-created for filesystem repair
$ ls -l mnt
drwx----- 2 root    root      12288 Apr 21 09:52 lost+found
# copy myinit to the filesystem on our virtual disk
$ cp myinit mnt/myinit
$ ls -l mnt
drwx----- 2 root    root      12288 Apr 21 09:52 lost+found
-rwxrwxr-x 1 root    root    769256 Apr 21 09:55 myinit
$ umount mnt
$ ls -l mnt
total 0
```


running our kernel with our init

```
# init=/myinit tells linux to run /myinit as the initial process
# quiet tells linux not to print diagnostic information as it boots
$ qemu-system-aarch64 -machine virt -cpu max -drive
  ↪ file=mydisk,format=raw,if=virtio -nographic -kernel mykernel -append
  ↪ 'init=/myinit root=/dev/vda rw rootwait'
hello from myinit
reboot: Power down
$
```

- we've successfully booted and shutdown our tiny system
- now we need more programs to run on our tiny system

Summary - Commands to Build a Tiny Virtual Machine

```
$ curl -s https://cdn.kernel.org/pub/linux/kernel/v6.x/linux-7.0.tar.xz | tar
  ↪ -Jxf -
$ curl -sL curl -sL
  ↪ https://raw.githubusercontent.com/buildroot/buildroot/master/board/
qemu/aarch64-virt/linux.config > linux-7.0/.config
$ make -C linux-7.0 olddefconfig
$ make -C linux-7.0 -j32
$ cp linux-7.0/arch/arm64/boot/Image mykernel
$ fallocate -l 128M mydisk
$ mkfs.ext2 mydisk
$ gcc myinit.c -static -o myinit
$ mkdir mnt
$ fuse2fs -o fakeroot mydisk mnt
$ cp myinit mnt/myinit
$ umount mnt
$ qemu-system-aarch64 -machine virt -cpu max -drive
  ↪ file=mydisk,format=raw,if=virtio -nographic -kernel mykernel -append
  ↪ 'init=/myinit root=/dev/vda rw rootwait'
```

Busybox

- busybox provides simplified versions of 270+ Unix utilities
- widely used on embedded & other systems, due to small footprint
- easy to download an already compiled busybox

```
$ curl -L -o busybox
↪ https://busybox.net/downloads/binaries/1.31.0-defconfig-multiarch-musl/
busybox-armv7m
$ ls -l busybox
-rw-rw-r-- 1 root root 1061344 Apr 21 10:00 busybox
$ chmod +x busybox
$ file busybox
busybox: ELF 32-bit LSB executable, ARM, EABI5 version 1 (SYSV), statically
↪ linked, stripped
```

Building Busybox

- also easy to compile from source

```
$ curl -sL https://busybox.net/downloads/busybox-1.36.0.tar.bz2 | tar -jxf -
$ cd busybox-1.36.0
$ find . -type f | wc -l
5231
$ find . -name '*.ch' | xargs cat | wc -l
314726
$ make defconfig
....
$ sed -i 's/# CONFIG_STATIC is not set/CONFIG_STATIC=y/' .config
# workaround busybox bug
$ sed -i 's/CONFIG_TC=y/CONFIG_TC=n/' .config
$ make -j8
....
$ cd ..
$ cp busybox-1.36.0/busybox busybox
$ ls -l busybox
-rwxrwxr-x 1 root root 2350536 Apr 21 10:06 busybox
$ file busybox
busybox: ELF 64-bit LSB executable, ARM aarch64, version 1 (GNU/Linux),
↳ statically linked, ..
```

- busybox provides simplified versions of 400+ Unix utilities
- you can run these commands as command-line arguments to busybox

```
$ ./busybox echo hello from Busybox
hello from Busybox
$ ./busybox cp myinit.c myinit.c.backup
$ ./busybox wc myinit.c.backup
      7      14      157 myinit.c.backup
```

Busybox - argv[0] trick

- more often busybox is run via a link, it looks at argv[0] and behaves appropriately

```
$ ln -s busybox echo
$ ln -s busybox cp
$ ln -s busybox wc
$ echo hello from Busybox
hello from Busybox
$ cp myinit.c myinit.c.backup
$ wc myinit.c.backup
      8      14      162 myinit.c.backup
```

Busybox - argv[0] trick - how it might work in Python

```
#!/usr/bin/python3
import os, shutil, sys
myname = os.path.basename(sys.argv[0])
if myname == "echo":
    print(*sys.argv[1:])
elif myname == "cp":
    shutil.copyfile(sys.argv[1], sys.argv[2])
elif myname == "rm":
    for pathname in sys.argv[1:]:
        os.unlink(pathname)
else:
    print(f"Unknown name: {myname}", file=sys.stderr)
```

[source code for argv0.py](#)

Programs Provided by Busybox

```
$ ./busybox --list | wc -l
402
$ ./busybox --list
[ [ acpid add-shell addgroup adduser adjtimex arch arp arping ascii ash awk
↵ base32 base64 basename bc beep blkdiscard blkid blockdev bootchartd brctl
↵ bunzip2 bzip2 bzip2 cal cat chat chattr chgrp chmod chown chpasswd chpst
↵ chroot chrt chvt cksum clear cmp comm conspy cp cpio crc32 crond crontab
↵ cryptpw ctyhack cut date dc dd dealloctv delgroup deluser depmod devmem
↵ df dhcprelay diff dirname dmesg dnsd dnsdomainname dos2unix dpkg dpkg-deb
↵ du dumpkmap dumpleases echo ed egrep eject env envdir envuidgid ether-wake
↵ expand expr factor fakeidentd fallocation false fatattr fbsset fbsplash
↵ fdflush fdformat fdisk fgconsole fgrep find findfs flock fold free
↵ freeramdisk fsck fsck.minix fsfreeze fstrim fsync ftpd ftpget ftpput fuser
↵ getfattr getopt getty grep groups gunzip gzip halt hd hdparm head hexdump
↵ hexedit hostid hostname httpd hush hwclock i2cdetect i2cdump i2cget i2cset
↵ i2ctransfer id ifconfig ifdown ifenslave ifplugd ifup inetd init insmod
↵ install ionice iostat ip ipaddr ipcalc ipcrm ipcsc iplink ipneigh iproute
↵ iprule iptunnel kbd_mode kill killall killall5 klogd last less link
↵ linux32 linux64 linuxrc ln loadfont loadkmap logger login logname logread
↵ losetup lpd lpq lpr ls lsattr lsmod lsof lspci lsscsi lsusb lzcat lzma
↵ lzop makedevs makemime man md5sum mdev msg microcom mim mkdir mkdosfs
↵ mke2fs mkfifo mkfs.ext2 mkfs.minix mkfs.vfat mknod mkpasswd mkswap mkttemp
↵ modinfo modprobe more mount mountpoint mpstat mt mv nameif nanddump
↵ nandwrite nbd-client nc netstat nice nl nmeter nohup nologin nproc nsenter
↵ nslookup ntpd od openvt partprobe passwd paste patch pgrep pidof ping
↵ ping6 pipe_progress pivot_root pkill pmap popmaildir poweroff powertop
↵ printenv printf ps pscan pstree pwd pwdx raidautorun rdate rdev readahead
↵ readlink readprofile realpath reboot reformime remove-shell renice reset
↵ resize resume rev rm rmdir rmmode route rpm rpm2cpio rtcwake run-init
↵ run-parts runlevel runsv runsvdir rx script scriptreplay sed seedrng
↵ sendmail seq setarch setconsole setfattr setfont setkeycodes setlogcons
↵ setpriv setserial setsid setuidgid sh shasum sha256sum sha3sum sha512sum
↵ showkey shred shuf slattach sleep smemcap softlimit sort split ssl_client
↵ start-stop-daemon stat strings stty su sulogin sum sv svc svlogd svok
↵ swapon swapoff switch_root sync sysctl syslogd tac tail tar taskset tcpsvd
↵ tee telnet telnetd test tftp tftpd time timeout top touch tr traceroute
↵ traceroute6 tree true truncate ts tsort tty ttysize tuncle ubiattach
↵ ubidetach ubienvol ubirename ubirmvol ubirsvol ubiupdatevol udhpc udhpc6
↵ udhpcd udpsvd uevent umount uname unexpand uniq unix2dos unlink unlzma
↵ unshare unxz unzip uptime users usleep uudecode uencode vconfig vi vlock
↵ volname w wall watch watchdog wc wget which who whoami whois xargs xxd xz
↵ xzcat yes zcat zcip
```


Adding Busybox to the Filesystem on our Virtual Disk

```
$ fuse2fs -o fakeroot mydisk mnt
$ mkdir mnt/bin
# add busybox to our virtual disk
$ cp busybox mnt/bin/
# create 400+ links to busybox on virtual disk
$ for p in $(./busybox --list);do ln -s ./busybox mnt/bin/$p; done
$ umount mnt
# init=/bin/sh says run busybox's shell as the first process
$ qemu-system-aarch64 -machine virt -cpu max -drive
↳ file=mydisk,format=raw,if=virtio -nographic -kernel mykernel -append
↳ 'root=/dev/vda rw rootwait init=/bin/sh console=ttyAMA0'
...
/ # ls -l /bin/sh
lrwxrwxrwx    1 517          517          7 Jul 28 04:57 /bin/sh -> busybox
/ # ls -l /bin/cat
lrwxrwxrwx    1 517          517          7 Jul 28 04:57 /bin/cat -> busybox
# we can now run 403 programs all of which are really busybox
/ # ls -l /bin | wc -l
403
```

Summary for Building & Installing Busybox

```
$ curl -sL https://busybox.net/downloads/busybox-1.36.0.tar.bz2 | tar -jxf -
$ make -C busybox-1.36.0 defconfig
$ sed -i 's/# CONFIG_STATIC is not
↳ set/CONFIG_STATIC=y;/s/CONFIG_TC=y/CONFIG_TC=n/' busybox-1.37.0/.config
$ make -C busybox-1.36.0 -j8
$ fuse2fs -o fakeroot mydisk mnt
$ mkdir mnt/bin
$ cp -p busybox-1.36.0/busybox mnt/bin/busybox
$ for p in $(mnt/bin/busybox --list);do ln -s busybox mnt/bin/$p; done
$ umount mnt
$ qemu-system-aarch64 -machine virt -cpu max -drive
↳ file=mydisk,format=raw,if=virtio -nographic -kernel mykernel -append
↳ 'root=/dev/vda rw rootwait init=/bin/sh console=ttyAMA0'
...
```

Some Special Linux Filesystems

- some commands need special “virtual” files provided by Linux, Unix philosophy *Everything is a file*

```
/ # ps
PID    USER      TIME  COMMAND
ps: can't open '/proc': No such file or directory
/ # sleep 5 &
/ # /bin/sh: can't open '/dev/null': No such file or directory
```

- **/dev** - pathnames for hardware devices.
- **/proc** - special filesystem with information about processes
- **/sys** - special filesystem with information about system

These are virtual filesystems provided by Linux.

Mounting Virtual filesystems

```
/ # mkdir /dev /proc /sys
/ # mount -t devtmpfs none /dev
/ # mount -t proc none /proc
/ # mount -t sysfs none /sys
/ # cat /proc/cpuinfo
processor      : 0
vendor_id     : AuthenticAMD
cpu family    : 15
model         : 107
model name    : QEMU Virtual CPU version 2.5+
...
/ # ls -l /dev/vda /dev/null /dev/random /dev/zero
crw-rw-rw-    1 0          0              1,   3 Jul 28 05:25 /dev/null
crw-rw-rw-    1 0          0              1,   8 Jul 28 05:25 /dev/random
brw-----    1 0          0              8,   0 Jul 28 05:25 /dev/vda
crw-rw-rw-    1 0          0              1,   5 Jul 28 05:25 /dev/zero
```

- **c** indicates character device - read/write bytes
- **b** indicates block devices - read/write blocks

some interesting “virtual” devices

- **/dev/null**

- writes do nothing (are ignored)
- reads return nothing

- **/dev/zero**

- reads return bytes containing 0

- **/dev/urandom**

- reads return random bytes

some interesting “virtual” devices

```
$ xxd /dev/null
```

```
$ xxd /dev/zero|head
```

```
00000000: 0000 0000 0000 0000 0000 0000 0000 0000 .....
00000010: 0000 0000 0000 0000 0000 0000 0000 0000 .....
00000020: 0000 0000 0000 0000 0000 0000 0000 0000 .....
00000030: 0000 0000 0000 0000 0000 0000 0000 0000 .....
00000040: 0000 0000 0000 0000 0000 0000 0000 0000 .....
00000050: 0000 0000 0000 0000 0000 0000 0000 0000 .....
00000060: 0000 0000 0000 0000 0000 0000 0000 0000 .....
00000070: 0000 0000 0000 0000 0000 0000 0000 0000 .....
00000080: 0000 0000 0000 0000 0000 0000 0000 0000 .....
00000090: 0000 0000 0000 0000 0000 0000 0000 0000 .....
```

```
$ xxd /dev/urandom|head
```

```
00000000: 16a0 e6c3 16ac d43d a258 de1f 9ba8 a24b .....=.X.....K
00000010: 5661 3488 a6e4 fa2f 4204 fb80 16ad e0ec Va4.... /B.....
00000020: 9eb2 e60b 7267 1250 1954 47a4 75bb 79bc ....rg.P.TG.u.y.
00000030: 410c 334a b38d 4801 550a 2c83 35a3 e30d A.3J..H.U.,.5...
00000040: d603 31b7 6062 6c54 3b6f 0e00 bd4a 765a ..1.`b!T;o...JvZ
00000050: cfe6 d39c 89ba 9a02 66cd 5044 f417 30da .....f.PD..0.
00000060: eba5 df10 223a b963 7ad4 160c ae06 7660 ....":.cz.....v`
00000070: a4c4 352e 0252 615c 8e17 7b30 2e48 6fb3 ..5..Ra\..{0.Ho.
00000080: f9d5 d4f7 2913 73a9 3042 07de dde5 3537 ....).s.0B....57
00000090: 686c fba5 f41a b66a 7b68 2d48 3077 c672 h!.....j{h-H0w.r
```

Aside - Tools for Managing Processes

- *process* is an instance of an executing program
- on Unix-like systems each process had a unique number (pid)
 - pid's are smallish non-negative integer
- **ps** ... show process information
- **kill** ... send a signal to a process
 - typically used to terminate a process
 - signal 9 always terminates process

```
# using kill to logout
```

```
$ ps
```

PID	TTY	TIME	CMD
344024	pts/2	00:00:00	bash
346137	pts/2	00:00:00	ps

```
$ kill -9 344024
```

Tools for Managing Processes

- **pgrep** ... print PIDs of processes matching selection criteria
 - **pgrep** send a signal to processes matching selection criteria
- **killall** ... also send a signal to a process with particular names
 - less powerful but more widely available than **kill**
- **top** ... real-time monitoring of running process
 - or more easy to use **htop**

```
# find processes with python in their name
$ pgrep python
10787
20060
25975
27475
# kill processes with 2 consecutive vowels (don't do this!)
$ pkill -9 '[aeiou][aeiou]'
# kill all programs named teams or zoom
$ killall zoom teams
```


Running 100 Processes Inside our Virtual Machine

- qemu is one process (running program) but it can simulate a machine running 100 processes

```
/ # cat >repeat.sh <<'eof'
#!/bin/sh
for j in $(seq 5)
do
    echo "Hello $j from process $1"
    sleep $((1 + RANDOM % 10))
done
eof
/ # chmod 700 repeat.sh
/ # for i in $(seq 100); do ./repeat.sh $i & done
....
```

Adding Networking to our System

- qemu's **-nic** option adds a virtual network card to our virtual machine
- take COMP3331/9331 to understand the networking commands

```
$ qemu-system-aarch64 -machine virt -nic user,model=virtio-net-pci -cpu max
↳ -drive file=mydisk,format=raw,if=virtio -nographic -kernel mykernel
↳ -append 'root=/dev/vda rw rootwait init=/bin/sh console=ttyAMA0'
/ # mkdir etc
/ # echo "nameserver 10.0.2.3" >/etc/resolv.conf
/ # ifconfig eth0 up 10.0.2.15
/ # route add default gw 10.0.2.2
/ # ifconfig eth0 up 10.0.2.15
# check networking works by getting today's weather
/ # wget -O- http://wttr.in
Connecting to wttr.in (5.9.243.187:80)
writing to stdout
Weather report: Sydney, Australia
...
# we now have networking, lets install a Linux distribution
```

Summary for Setting up Special Filesystems & Networking

```
$ qemu-system-aarch64 -machine virt -nic user,model=virtio-net-pci -cpu max
↳ -drive file=mydisk,format=raw,if=virtio -nographic -kernel mykernel
↳ -append 'root=/dev/vda rw rootwait init=/bin/sh console=ttyAMA0'
/ # mkdir -p /dev /proc /sys /etc
/ # mount -t devtmpfs none /dev
/ # mount -t proc none /proc
/ # mount -t sysfs none /sys
/ # echo "nameserver 10.0.2.3" >/etc/resolv.conf
/ # ifconfig eth0 up 10.0.2.15
/ # route add default gw 10.0.2.2
/ # ifconfig eth0 up 10.0.2.15
```

/etc/passwd - user “database”

User information in **/etc/passwd**

Password hashes in **/etc/shadow**

Every user has unique number: **uid**

```
$ sed 2q /etc/passwd
root:x:0:0:root:/root:/bin/bash
daemon:x:1:1:daemon:/usr/sbin:/usr/sbin/nologin
$ sed 2q /etc/shadow
root:$6$YiSiP7Pehz8a0e...../:18379:0:99999:7:::
daemon:*:18362:0:99999:7:::
```

- better to not edit **/etc/passwd** & **/etc/shadow** directly
- instead use (distribution-specific) tools, e.g on Debian-like systems:
 - add users with **adduser**
 - remove users with **deluser**

Group information in **/etc/group**

```
$ head /etc/group
root:x:0:
daemon:x:1:
bin:x:2:
sys:x:3:
adm:x:4:
tty:x:5:
```

- Each group has unique number: **gid**
- Better to not edit **/etc/group** directly
- instead use (distribution-specific) tools, e.g on Debian-like systems:
- Add users to groups with **adduser**
- Also **addgroup delgroup**

fsck - repair a file-system

- Power failure or other unexpected events may leave a filesystem in inconsistent state.
- **fsck** (file system check) checks and repairs a file-system.

```
# copy a random byte into our virtual disk to simulate corruption
$ dd if=/dev/urandom of=mydisk bs=1 seek=1024 count=1 conv=notrunc
$ fuse2fs -o fakeroot mydisk mnt
mydisk: The ext2 superblock is corrupt.
Please run e2fsck -fy mydisk.
# repair file system
$ fsck.ext2 mydisk
e2fsck 1.46.4 (18-Aug-2021)
ext2fs_open2: The ext2 superblock is corrupt
fsck.ext2: Superblock invalid, trying backup blocks...
mydisk was not cleanly unmounted, check forced.
...
Pass 1: Checking inodes, blocks, and sizes
Deleted inode 13 has zero dtime.  Fix? yes
...
# filesystem will now mount
$ fuse2fs -o fakeroot mydisk mnt
```

- File system should not be in use (unmounted)
- **Beware:** dangerous operation - have backups!

running a program with a different root directory

- Linux **namespace** is the view of a system resource given to a process
- **namespaces** include filesystem (mount), processes (PID) and network
- Linux unshare system call allows a process to be run with a different **namespace**
 - e.g allows proces to be run with a different root directory

```
$ mkdir tiny_root/  
$ echo "hello from tiny root" >tiny_root/hello.txt  
$ ls tiny_root  
hello.txt  
$ unshare --map-root-user --root=tiny_root /bin/sh  
unshare: failed to execute /bin/sh: No such file or directory  
# failed because no /bin/sh once root directory changed  
$ ls tiny_root/bin/sh  
ls: cannot access 'tiny_root/bin/sh': No such file or directory
```

running a program with a different root directory

```
# add busybox to tinyroot
$ mkdir tiny_root/bin
$ cp busybox tiny_root/bin/
# create links for the 400 programsu busybox provides
$ for p in $(./busybox --list); do ln -s busybox tiny_root/bin/$p;done
$ ls -l tiny_root/bin/sh
lrwxrwxrwx 1 root root 7 Apr 18 10:14 tiny_root/bin/sh -> busybox
$ unshare --map-root-user --root=tiny_root /bin/sh
# now in shell which sees tiny_root as /
$ ls /
bin
hello.txt
$ cat /hello.txt
hello from tiny root
```


- Linux containers use namespaces to run processes in a different “world”
- you can run a process with effectively:
 - different root directory
 - e.g. /usr/bin can look different to process
 - e.g different process ids
 - e.g different view of network
 - different uid
 - specified resource limits
- allows a program to be run which needs different packages to those installed

Docker & Podman - Tools for Running Containers

- Docker popular set of tools for working with Linux containers
 - easy to use, but heavyweight (requires daemon)
- Podman open source equivalent for Red Hat
 - other open source tools may be useful depending on needs
- both use a union file system in clever way
 - overlays images so base images can be reused
- can specify dependencies for a program and produce self-contained image
 - e.g. can specify program requires python-3.9
- can run image on any Linux, Windows or OSX system with Docker installed
 - independent of what software is installed on that platform
- **hub.docker.com** provides sharing similar to **github.com**
- Docker great for many purposes, but heavyweight (requires daemon)
- good to experiment with over the term-break
 - containers hard to use at CSE
 - disk space issues if every student has containers
 - docker not available - requires root
 - podman doesn't work with NFS
 - easy to install docker or podman on your own machine

Running Shells Command Inside and Outside a Container

```
$ whoami
root
$ pwd
/home/comp2041
$ grep haibo /etc/passwd
haibo:x:1000:1000:,,,:/home/haibo:/bin/bash
# or podman run -it --rm alpine
$ docker run -it --rm alpine
...
/ # whoami
root
/ # pwd
/
/ # find /|wc -l
65716
/ # grep haibo /etc/passwd
/ # ls /home/comp2041
ls: /home/comp2041: No such file or directory
```

Mounting A Directory Inside a Container

```
$ cat hello.txt
Hello COMP(2041|9044)
# or podman run -it -v mnt alpine
$ docker run -it -v mnt alpine
/ # ls /mnt
hello.txt
/ # cat /mnt/hello.txt
Hello COMP(2041|9044)
/ # echo hello from a container >/mnt/new.txt
/ # exit
$ cat new.txt
hello from a container
```

Specifying a Container Image with a Dockerfile

- Docker has a specification language for creating containers images
 - series of commands in a file (usually) named **Dockerfile**
- **FROM** command - use pre-existing Docker image used as starting point
 - often image with linux distribution installed (Linux Alpine, Ubuntu, Debian ...)
 - and perhaps an application such as webserver or database (nginx, postgres, ...)
- **ADD** command - copy files into image
- **RUN** command - run shell commands as part of building image
- **ENTRYPOINT** command - run command when container starts

Example Dockerfile

```
# use Alpine Linux as the base of our image
FROM alpine
RUN \
    apk update &&\
    # install apache web server
    apk add apache2 curl &&\
    # a configuration file Apache needs
    echo ServerName my-web-server >/etc/apache2/conf.d/localhost.conf
# add a file to the image for our webserver to serve
ADD hello.txt /var/www/localhost/htdocs/hello.txt
# run web-server plus shell when container started
ENTRYPOINT \
    /usr/sbin/httpd &&\
    ash &&\
    killall httpd
```

[source code for Dockerfile](#)

Example - Building and Running the Container

```
# 127.0.0.1 is a special network address for the local machine
$ curl http://127.0.0.1/hello.txt
curl: (7) Failed to connect to 127.0.0.1 port 80 after 0 ms: Connection
↪ refused
$ docker build -t my_apache .
$ docker run -it --rm my_apache
/ # wget -O- http://127.0.0.1/hello.txt
hello from inside a container
```

In another window try to access web server in container

```
$ curl http://127.0.0.1/hello.txt
curl: (7) Failed to connect to 127.0.0.1 port 80 after 0 ms: Connection
↪ refused
$
```

Example - Making a Network Port visible Outside the Container

```
$ curl http://127.0.0.1:6789/hello.txt
curl: (7) Failed to connect to 127.0.0.1 port 6789 after 0 ms: Connection
↪ refused
$ docker run -it -p 6789:80 --rm my_apache
/ # tail -f /var/log/apache2/access.log
172.17.0.1 - - [04/Aug/1997:01:15:18 +0000] "GET /hello.html HTTP/1.1" 200 9
↪ "-" "curl/7.88.1"
```

In another window

```
$ curl http://127.0.0.1:6789/hello.txt
hello from a webserver inside a container
```


Example - Supplying Webpages from Outside the Container

```
$ mkdir /tmp/content
$ echo I love shell > /tmp/content/webpage.txt
$ docker run -it -p 6789:80 -v /tmp/content:/var/www/localhost/htdocs --rm
  ↪ my_apache
/ # tail -f //var/log/apache2/access_log
172.17.0.1 - - [03/Aug/1997:01:15:18 +0000] "GET /5.html HTTP/1.1" 200 9 "-"
  ↪ "curl/7.88.1"
```

In another window

```
$ curl http://127.0.0.1:6789/webpage.txt
I love shell
```