

Multi-file C Programs

- Large C programs spread across many C files
e.g. Linux operating system has 50,000+ **.c** files.
- Files provide a *de facto* module system in C.
- C functions can be called from any file, unless **static**
Declaring functions **static**
 - ▶ avoids name clashes in huge programs
 - ▶ makes programs more readable/maintainable
- No checking of function parameters & return types between files
- By convention include **.h** files used to share information between **.c** files
ensure types match between files.

Include Files

- Include **.h** files contain:
 - ▶ function prototypes
 - ▶ type definitions
 - ▶ `#define`'s
- **.h** files should not contain code (function definitions)
- `#include` with `"` used to incorporate **.h** file
put `#include` at top of **.c** file

Example: Include File

answer.h

```
int answer(double x);
```

answer.c

```
#include "answer.h"
int answer(double x) {
    return x * 21;
}
```

main.c

```
#include "answer.h"

int main(void) {
    printf("answer(2) = %d\n", answer(1));
    return 0;
}
```

Multi-file Compilation

```
$ gcc main.c answer.c -o answer
$ ./answer
42
```

Can also compile file separately creating `.o` files which contain machine code for one file.

```
$ gcc -c main.c
$ gcc -c answer.c
$ gcc main.o answer.o -o answer
$ ./answer
42
```

Useful with huge programs because faster to re-compile only part changed since last compilation.